WIZOIL SYNTINT 5W-30 A5

DESCRIPTION:

WIZOIL SYNTINT 5W-30 A5 is a high-performance fully synthetic motor oil especially developed for passenger cars from Ford, Volvo, Jaguar and Land Rover with gasoline or diesel engines.

APPLICATION:

WIZOIL SYNTINT 5W-30 A5 is suitable for use in automotive gasoline and diesel engines where oils with the specifications according to ACEA A5/B5 are recommended. This unique formulation meets the requirements of Ford WSS-M2C913-D.

ADVANTAGES:

- Excellent thermal and oxidation stability
- Increased protection against wear
- Potential for fuel saving

PRODUCT PERFORMANCE CLAIMS:

- ACEA A5/B5-21;
- API SL/CF

- FORD WSS-2C913-D;
- RN 0700;
- STJLR.03.5003



TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL SYNTINT 5W-30 A5
Density @ 15C, Relative	ASTM D 4052	g/ml	0.85
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	55
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	9,7
Viscosity Index	ASTM D 2270	-	162
Viscosity, CCS -35°C (0W)	ASTM D 5293	mPa·s	4750
Flash Point	ASTM D 92	°C	204
Pour Point	ASTM D 97	°C	-42

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 17.07.2025