WIZOIL ATF DEXRON VI

DESCRIPTION:

High-performance fully synthetic automatic transmission fluid WIZOIL ATF DEXRON VI is recommended for use in passenger cars and LCV automatic transmissions that require a GM Dexron VI or earlier generation fluid.

APPLICATION:

WIZOIL ATF DEXRON VI is suitable for use in the majority of 6,7,8 and 9 speed automatics of European cars, meaning it is suitable for use in nearly all passenger car automatic transmissions. It delivers enhanced protection and a smoother drive for longer.

ADVANTAGES:

Provides:

- Superior high temperature protection to effectively resist oxidation
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Outstanding friction durability for consistent shift performance for the life of the fluid
- Enhanced friction durability for smooth transmission performance

PRODUCT PERFORMANCE CLAIMS:

- GM DEXRON® VI;
- FORD MERCON®LV;
- TOYOTA TYPE T-III;
- NISSAN Matic Fluid J/Matic Fluid K;
- MAZDA ATF M-III/ATFM-V;
- JASO M315-2013 1A-LV;
- HYUNDAI / KIA SP-III;
- LAND ROVER Texaco N402;
- SUBARU ATF, ATF HP;
- ALLISON C4;
- JAGUAR Idemitsu K17;
- BMW ETL- 7045E, ETL-8072B;
- MB 236.5/236.6/ 236.7

TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL ATF DEXRON VI
Density @ 15C, Relative	ASTM D 4052	g/ml	0.844
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	28,8
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	6,008
Viscosity Index	ASTM D 2270	-	162
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-45
Viscosity, Brookfield @ -40C	ASTM D 2983	mPa*c	13000
Colour	Visual		red

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 05.05.2025