WIZOIL CVT MULTI-V

DESCRIPTION:

High-performance fully synthetic multi-vehicle CVT fluid is formulated from selected high-quality synthetic base oils combined with an advanced additive system designed to meet the service fill needs of the broadest range of wet continuously variable (step-less) transmissions in vehicles from European and Asian car manufacturers.

APPLICATION:

WIZOIL CVT MULTI-V is recommended for service fill use in in a broad range of belt or chain type continuously variable transmissions.

ADVANTAGES:

- Excellent protection of the transmission against wear, rust and corrosion helps preserve the transmission life
- Excellent flow properties provide immediate lubrication and protection at cold start-up
- Excellent oil oxidation and shear stability contributes to long fluid life
- Superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness

PRODUCT PERFORMANCE CLAIMS:

SUITABLE FOR USE:

- MAZDA CVTF 3320;
- NISSAN NS-1/NS-2/NS-3;
- TOYOTA CVT FLUID TC, FE;
- FORD CVT23, CVT30, WSS-M2C-933-A/ Motorcraft XT-7-QCVT, MERCON C;
- MITSUBISHI DiaQueen CVT FLUID- J1/ CVT FLUID- J4;
- SUZUKI CVT Fluid 3320/ GREEN 1/GREEN 2/TC;
- SUZUKI NS-2;
- HONDA HMMF/HCF-2;
- VW/AUDI (TL 52180: G 052 180; G 052 516);
- BMW EZL799/799A;
- DAIHATSU AMMIX CVT FLUID DC/DFE;
- CHRYSLER/DODGE/JEEP NS-2/CVTF +4/ MOPAR CVTF +4;
- GM/SATURN DEX-CVT/CVTF- Green 2;
- RENAULT ELFMATIC;
- IDEMITSU CVTS-EX1;
- PUNCH EZL 799/EZL 799A;
- SHELL GREEN 1V;
- SUBARU I-CVTF/LINEARTRONIC CVTF (K0425Y0710, CV-30)/e- CVTF
- MINI COOPER EZL799/799A/ZF CVT V1

TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL CVT MULTI-V
Density @ 15C, Relative	ASTM D 4052	g/ml	0.848
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	38,1
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	7,2
Viscosity Index	ASTM D 2270	-	156
Flash Point	ASTM D 92	°C	210
Pour Point	ASTM D 97	°C	-42
Viscosity, Brookfield @ -40C	ASTM D 2983	mPa*c	18000
Colour	Visual		green

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 05.05.2025