WIZOIL SYNTINT 0W-40 A3/B4

DESCRIPTION:

High-performance synthetic motor oil contains ultra-pure base oil and a technologically advanced additives which provides an outstanding wear protection, excellent low temperature performance and enhanced fuel economy.

APPLICATION:

WIZOIL SYNTINT 0W-40 A3/B4 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, API SQ or earlier specification 0W-40 lubricant.

ADVANTAGES:

Provides:

- Outstanding wear protection under a wide variety of operating conditions
- Fast and easy start in extreme temperature conditions
- Less fuel and oil consumption
- Extra cleaning performance

PRODUCT PERFORMANCE CLAIMS:

- ACEA A3/B4;
- API SQ

- MB 226.5/229.3/229.5;
- VW 502 00/505 00;
- RN 0700/0710;
- Porsche A40;
- BMW LL-01;
- FORD WSS-M2C937-A



TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL SYNTINT 0W-40 A3/B4
Density @ 15C, Relative	ASTM D 4052	g/ml	0.844
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	76
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	13,3
Viscosity Index	ASTM D 2270	-	180
Viscosity, CCS -35°C (0W)	ASTM D 5293	mPa·s	5940
Flash Point	ASTM D 92	°C	212
Pour Point	ASTM D 97	°C	-44

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 01.06.2026