WIZOIL SYNTINT 0W-20 GF-6A

DESCRIPTION:

WIZOIL SYNTINT 0W-20 GF-6A is energy conserving fully synthetic motor oil. Developed for Japanese, Korean, Chinese and American vehicles with gasoline and/or hybrid engines. It provides fuel economy and outstanding wear protection under a wide variety of operating conditions.

APPLICATION:

WIZOIL SYNTINT 0W-20 GF-6A is suitable for gasoline and/or hybrid passenger cars and light duty commercial engines produced by Japanese, Korean and other manufacturers. WIZOIL SYNTINT 0W-20 GF-6A meets or exceeds the requirements of 'API SP Resource Conserving' industry standard therefore contributing to engine fuel efficiency and helping address LSPI (Low Speed Pre-Ignition) making it a preferred choice for downsized direct injection turbocharged gasoline engines

ADVANTAGES:

- Less fuel and oil consumption
- Helps to reduce oil aging resulting in long lasting protection
- Maximum engine performance
- Efficient keep-clean additive technology helps reduce harmful deposit and sludge formation, offering extended engine life
- Quick cold weather starting and fast protection helps to extend engine life

PRODUCT PERFORNANCE CLAIMS:

- API SP (RC);
- ILSAC GF-6A

TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL SYNTINT 0W-20 GF-6A
Density @ 15C, Relative	ASTM D 4052	g/ml	0.844
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	44
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	8,4
Viscosity Index	ASTM D 2270	-	172
Viscosity, CCS -35°C (0W)	ASTM D 5293	mPa·s	5500
Flash Point	ASTM D 92	°C	222
Pour Point	ASTM D 97	°C	-42

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 01.06.2026