WIZOIL SYNTINT 5W-30 A3/B4

DESCRIPTION:

WIZOIL SYNTINT 5W-30 A3/B4 is a fully synthetic motor oil developed for modern gasoline and diesel engines.

APPLICATION:

WIZOIL SYNTINT 5W-30 A3/B4 is suitable for passenger cars and LCV with gasoline or diesel engines turbocharged or naturally aspirated, direct or indirect injection.

ADVANTAGES:

- Less fuel and oil consumption
- Increased protection against wear
- Excellent thermal and oxidation stability

PRODUCT PERFORMANCE CLAIMS:

- ACEA A3/B4;
- API SP

- VW 502 00/505 00;
- MB 229.3/229.5;
- RN 0700/0710



TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL SYNTINT 5W-30 A3/B4
Density @ 15C, Relative	ASTM D 4052	g/ml	0.855
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	73
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	12
Viscosity Index	ASTM D 2270	-	161
Viscosity, CCS -30°C (5W)	ASTM D 5293	mPa·s	6400
Flash Point	ASTM D 92	°C	227
Pour Point	ASTM D 97	°C	-43

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 01.06.2026