WIZOIL SYNTINT 5W-30 GF-7A

DESCRIPTION:

WIZOIL SYNTINT 5W-30 GF-7A is energy conserving fully synthetic motor oil. Developed for Japanese, Korean, Chinese and American vehicles with gasoline and/or hybrid engines. It provides fuel economy and outstanding wear protection under a wide variety of operating conditions.

APPLICATION:

WIZOIL SYNTINT 5W-30 GF-7A is suitable for gasoline passenger cars and light duty commercial engines produced by Japanese, Korean and other manufacturers.

ADVANTAGES:

- Less fuel and oil consumption
- Maximum engine performance
- Efficient keep-clean additive technology helps reduce harmful deposit and sludge formation, offering extended engine life
- Fast and easy start in extreme temperature condition

PRODUCT PERFORMANCE CLAIMS:

- ILSAC GF-7A;
- API SQ

- FORD WSS-M2C961-A;
- FORD WSS-M2C946-B1;
- CHRYSLER MS 6395

TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL SYNTINT 5W-30 GF-7A
Density @ 15C, Relative	ASTM D 4052	g/ml	0.848
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	63,9
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	11
Viscosity Index	ASTM D 2270	-	174
Viscosity, CCS -30°C (5W)	ASTM D 5293	mPa·s	3900
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-45

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 06.10.2026