WIZOIL SYNTINT 5W-40 A3/B4

DESCRIPTION:

WIZOIL SYNTINT 5W-40 A3/B4 is a fully synthetic motor oil developed for modern gasoline and diesel engines.

APPLICATION:

WIZOIL SYNTINT 5W-40 A3/B4 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification SAE 5W-40 lubricant.

ADVANTAGES:

- Makes cold starting easier
- Advanced anti-wear additive technologies offer reliable engine wear protection
- Provide continuous protection for different driving conditions, styles and temperatures

PRODUCT PERFORMANCE CLAIMS:

- ACEA A3/B4;
- API SP

- VW 502 00/505 00;
- MB 229.3/229.5;
- RN 0700/0710



TYPICAL CHARACTERISTICS:

NAME	Method	Units	WIZOIL SYNTINT 5W-40 A3/B4
Density @ 15C, Relative	ASTM D 4052	g/ml	0.847
Viscosity, Kinematic 40°C	ASTM D 445	mm^2/s	86,44
Viscosity, Kinematic 100°C	ASTM D 445	mm^2/s	14,45
Viscosity Index	ASTM D 2270	-	174
Viscosity, CCS -30°C (5W)	ASTM D 5293	mPa˙s	4922
Flash Point	ASTM D 92	°C	224
Pour Point	ASTM D 97	°C	-50

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. No responsibility is taken by either WIZOIL plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Version 06.10.2026